

P-24-12, P-36-12 NEMA 12 ENCLOSURES U.L. Listed

General purpose enclosures for electric and pneumatic controls, instruments, and components. These enclosures provide protection from dust, dirt, oil, and water.

- NEMA 12, UL 50.
- Seams continuously welded and ground smooth; no holes or knockouts.
- Seamless, watertight gasket for tight seal.
- Baked on enamel finish over 16 gauge steel.
- Door clamps and key locking latch for extra security.
- Removable 16 gauge subpanel with mounting holes.
- Cabinet can be positioned for either left or right door opening.
- Mounting flanges on top and bottom of cabinet.



APPROVALS: NEMA 12; UL 50 Listed.

CONSTRUCTION:

Cabinet & Door: 16 gauge steel.

Subpanel: 16 gauge galvaneal steel with 1/8" OD (3.2mm) holes on 2" (51mm) centers.

Door Hinge: Continuous piano hinge.

Door Latch: Two screw clamps.

Door Lock: Key operated latch, 2 keys provided.

Knockouts: None.

MOUNTING: Surface using mounting holes in flanges on top and bottom of cabinet.

FINISH: Powder coated, baked on enamel.

COLOR: Tan.

- 11 to 20 pounds lighter weight than Hoffman and comparable NEMA 12 enclosures.
- P-24-12 with subpanel weighs 36 lbs. P-36-12 with subpanel weighs 59 lbs.
- Lighter weight often difference between requiring 1 or 2 persons to mount and install.
- Key lock with 2 keys included. Security without need to provide own padlock.
- Cabinet can be mounted first and removable subpanel with components added later.

Model	Cabinet – Inches (cm)			Subpanel – Inches (cm)		Weight w/ subpanel
	Height	Width	Depth	Height	Width	
P-24-12	24" (61)	20" (50.8)	6" (15.3)	22" (55.9)	18" (45.7)	36 lbs (16.4 kg)
P-36-12	36" (91.5)	24" (61)	6" (15.3)	34" (86.4)	22" (55.9)	59 lbs (26.9 kg)